

## **Mulching Heads**

**IMH Series** 





# IMH Mulching Heads

Indeco's new IMH series of hydraulically driven, boommounted mulching heads are specifically designed for a broad range of land clearing, site preparation, invasive vegetation species management, storm damage removal and clean-up applications. Tailored to fit a wide range of carriers from 5 to 50 tons, the IMH series is available in a number of direct-drive and belt-driven high-performance models and features HARDOX® components and bodies for optimal service life and lasting reliability.


Achieving greater productivity and cost-efficiency than a dedicated crew of workers with chainsaws and chippers, IMH Mulching Heads fully leverage your existing equipment investments by utilizing the excavator, back-hoe or skid-steer auxiliary hydraulics to turn your existing machine into a powerful land-clearing tool.

With a low initial cost, single man/machine operation for reduced processing costs and ease of use, the IMH series requires no additional specialized machinery and can be used on multiple machines to deliver a superior return on investment for your mulching applications.

In addition to superior productivity gains, mulching with the Indeco IMH series is also a more environmentally friendly process than conventional burning by putting back unwanted vegetation into the ecosystem as mulch.

This protects newly cleared areas from wind and rain erosion while providing the soil with beneficial microorganisms.





# IMH for excavators





Technical Data	IMH 12	IMH 15
Type of carrier	4 5	4 5
Cutting width	40 in	42 in
GPM range	25 ÷ 38 gpm	35 ÷ 52 gpm
Number of teeth	38	42
Drum diameter	8 in	12 in
Motor specification	Fixed Displacement	Variable Displacement
Transmission	Direct	Belt
Working pressure	3500 ÷ 5000 psi	3500 ÷ 5000 psi
Attachment operating weight*	2320 lbs	3300 lbs
Excavator weight	12 ÷ 18 tons	18÷ 29 tons

<sup>\*</sup>The attachment operating weight includes mounting bracket compatible with Indeco construction standards. Any differences in weight may be due to a different mounting bracket configuration.

Carrier key















Technical Data	IMH19	IMH 28
Type of carrier	5	5
Cutting width	42in	50 in
GPM range	50 ÷ 68 gpm	50 ÷ 70 gpm
Number of teeth	42	48
Drum diameter	12 in	18 in
Motor specification	Fixed Displacement	Fixed Displacement
Transmission	Belt	Belt
Working pressure	3500 ÷ 5000 psi	3500 ÷ 5000 psi
Attachment operating weight*	340O lbs	4600 lbs
Excavator weight	19÷35 tons	35 ÷ 45 tons

N.B. All illustrations and numerical data in this catalog are purely indicative and subject to change at our discretion and without notice. We therefore reserve the right to modify them with a view to improving and continuously developing our product.

## compatibility

Suggested uses on machines with an overall weight (in tons):

IMH 12 11 18 **IMH 15** 15 25 **IMH 19**19 30

IMH 28 28 45

## **Applications**

### Land clearing

IMH Mulching Heads are the perfect tools for clearing, cleaning up and periodically maintaining areas subject to becoming overgrown by vegetation. These can include pipelines, railway lines, ski slopes, electricity pylons and highways, as well as residential and commercial green areas. Powerful and easy to handle, they make it possible to take action quickly and efficiently, ensuring optimum results with minimum effort.

#### **Forestry**

Enjoying nature means first of all making it accessible shaping it to our needs and making sure that it can develop properly.

IMH Mulching Heads are useful tools for jobs involving green area maintenance, undergrowth clearance, firebreak creation and upkeep, as well as tree, brush, vegetation and branch clearing.

#### **Gardening & Landscaping**

IMH Mulching Heads and SG Stump Grinders are ideal tools in special applications involving reshaping the landscape such as golf course creation and upkeep, hedgerow rejuvenation, as well as stump, root and logging residue removal.













### The full range of other Indeco products

Products		Weigl	Weight	
IFP	8 X	1650	lb	
IFP	13 X	2900	lb	
IFP	19 X	4000	lb	
IFP	28 X	6200	lb	
IFP	35 X	7600	lb	
IFP	45 X	10050	lb	
IRP	5 X	1300	lb	
IRP	11 X	2550	lb	
IRP	18 X	3750	lb	
IRP	23 X	5100	lb	
IRP	29 X	6500	lb	
IRP	36 X	7950	lb	
IRP	45 X	9900	lb	
IMP*	15	3300	lb	
IMP*	20	4600	lb	
IMP*	25	5300	lb	
IMP*	35	7700	lb	

Products		Weight	
IMP*	45	9900	lb
IHC	50	450	lb
IHC	70	1000	lb
IHC	75	1100	lb
IHC	150	2150	lb
IHC	250	2850	lb
IHC R	50	950	lb
IHC R	70	1400	lb
IHC R	75	1500	lb
IHC R	150	2650	lb
IHC R	250	3350	lb
IMG S**	400	850	lb
IMG S**	600	1300	lb
IMG S**	1200	2550	lb
IMG S**	1700	3550	lb
IMG S**	2300	4800	lb
IMG S**	2800	5850	lb

Products		Weight	
ISS***	10/20	5280	lb
ISS***	20/30	8030	lb
ISS***	25/40	10560	lb
ISS***	30/50	13420	lb
ISS***	35/60	17160	lb
ISS***	45/90	22880	lb
IMH	5	1180	lb
IMH	6	1220	lb
IMH	8	1310	lb
IMH	10	1620	lb
IMH	12	2320	lb
IMH	15	3300	lb
IMH	19	3400	lb
IMH	28	4600	lb
IMH	3.5 SS	3090	lb
IMH	SG16	1850	lb
IMH	SG20	1850	lb

<sup>\*</sup>Crusher configuration - \*\*\*Sorter configuration - \*\*\*Third-member configuration

INDECO NORTH AMERICA 135 Research Drive Milford CT, 06460 ph. (203) 713-1030 - fax (203) 713-1040



www.indeco-breakers.com